

Panasonic

DM SERIES

32 inch LH-32DM300DX

RM SERIES

32 inch LH-32RM1DX

43 inch LH-43RM1DX

49 inch LH-49RM1DX

55 inch LH-55RM1DX

RISE. ACROSS VERTICALS.



ENTER THE NEXT LEVEL OF BUSINESS PRODUCTIVITY

COMMERCIAL LED DISPLAYS

Commercial LED Displays have propelled Business Efficiency, Retail Experience, Information Dissemination and Security Surveillance to the next level.

It's time to take the leap.

Product Specification for RM Series of LED Display Monitor

	Model No.	LH-32DM300DX	LH-32RM1DX	LH-43RM1DX	LH-49RM1DX	LH-55RM1DX
DISPLAY	Screen Size	32-inch	32-inch	43-inch	49-inch	55-inch
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9
	Backlight Scanning	100Hz	100Hz	100Hz	100Hz	100Hz
	Resolution	1920 x 1080 pixels	1366 x 768 pixels	1920 x 1080 pixels	1920 x 1080 pixels	1920 x 1080 pixels
	Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
TERMINAL	VIDEO IN	RCA X 1	RCA X 1	RCA X 1	RCA X 1	RCA X 1
	AUDIO IN (L/R)	RCA Pin Type X 2	RCA Pin Type X 2	RCA Pin Type X 2	RCA Pin Type X 2	RCA Pin Type X 2
	HDMI IN	TYPE A Connectors X 3	HDMI 1.4 X 2	HDMI 1.4 X 2	HDMI 1.4 X 3	HDMI 1.4 X 3
	USB Input	USB 2.0 X 2	USB 2.0 X 1	USB 2.0 X 1	USB 2.0 X 2	USB 2.0 X 2
	RS232C	NO	Yes	Yes	Yes	Yes
	HDMI CEC	Yes	Yes	Yes	Yes	Yes
	VGA IN	Yes	Yes	Yes	Yes	Yes
	PC AUDIO IN	Yes	Yes (1) (Share with AC)	Yes (1) (Share with AC)	Yes (1) (Share with AC)	Yes (1) (Share with AC)
GENERAL	Power Requirements	AC 110~240V,50/60Hz	AC 110~240V,50/60Hz	AC 110~240V,50/60Hz	AC 110~240V,50/60Hz	AC 110~240V,50/60Hz
	Rated Power Consumption	65W	50W	74W	100W	120W
	Stand By condition	< 0.5W	< 0.5W	< 0.5W	< 0.5W	<0.5W
	Built -in Speakers	Full range 16W (8w+8W)(10%THD)	Full range 20W (10W+10W)(10%THD)	Full range 20W (10W+10W)(10%THD)	20W (10W+10W) (10%THD)	20W (10W+10W) (10%THD)
	Dimensions(WXDXH) W Pedestal	732 X 165.5 X 466 mm	733.4 X 193.2 X 474mm	974.5 X 218.9 X 617.1mm	1104.2 X 270.8 X 692.4mm	1242.9 X 270.5 X 769.93mm
	Dimensions(WXDXH) W/O Pedestal	732 X 61 X 432 mm	733.4 X 85.1 X 438.5mm	974.5 X 85.8 X 575.6mm	1104.2 X 91.6 X 648.3mm	1242.9 X 90.1 X 727.9mm
	Weight (w Pedestal)	5.3 kg	4.0 Kg	8.8 Kg	11.5 Kg	13.8 Kg
	Gross Weight	6.6 kg	5.9 Kg	11.3 Kg	15.2 Kg	17.7 Kg
	Cabinet Color	Black	Black	Black	Black	Black
	VESA Mount	100 X 100 mm	100 X 100 mm	200 X 100 mm	200 X 200 mm	300 X 200 mm
	Operating Environment	Operating Temperature : 0°C to 40°C	Operating Temperature : 0°C to 40°C	Operating Temperature : 0°C to 40°C	Operating Temperature : 0°C to 40°C	Operating Temperature : 0°C to 40°C
		Operating Humidity : 20% to 80%	Operating Humidity : 20% to 80%	Operating Humidity : 20% to 80%	Operating Humidity : 20% to 80%	Operating Humidity : 20% to 80%
	Storage Environment	Temperature : -15°C to 60°C	Temperature : -15°C to 60°C	Temperature : -15°C to 60°C	Temperature : -15°C to 60°C	Temperature : -15°C to 60°C
		Humidity : 20% to 90% (noncondensation)	Humidity : 20% to 80% (noncondensation)	Humidity : 20% to 80% (noncondensation)	Humidity : 20% to 90% (noncondensation)	Humidity : 20% to 90% (noncondensation)
	SAFETY REGULATIONS	IS 13252:2010	IS 13252:2010	IS 13252:2010	IS 13252:2010	IS 13252:2010
INCLUDED ACCESSORIES	AC cord	Yes	Yes	Yes	Yes	Yes
	Operating Manual	Yes	Yes	Yes	Yes	Yes
	Remote	Yes	Yes	Yes	Yes	Yes
	Batteries	Yes	Yes	Yes	Yes	Yes
	Table Mount	Yes	Yes	Yes	Yes	Yes

* Bluetooth Keyboard Connectivity

Panasonic

Corporate Office:

Panasonic India Pvt. Ltd.
12th floor, Ambience Island

NH-8, Gurgaon-122002, Haryana, India

For Sales Enquiry : pi_ssd_dsg@in.panasonic.com Ph : 0124-4751300

For more information about Panasonic Display,

Please visit : panasonic.avc/projector



www.facebook.com/panasonicindia
www.twitter.com/panasonicindia



Service Helpline
1800-419-0373



www.panasonic.co.in
helpline@in.panasonic.com



INSIST ON A PANASONIC INDIA
WARRANTY CARD